

Art.602 **ASTAR GRAFIATO**

Water-based primer for exterior walls

GENERAL SPECIFICATIONS:

Filling and leveling primer for walls before painting with graffiti, based on synthetic resins and fillers. Product which can be used on all types of surfaces and can be diluted with water.

ADVICE:

- Protect the product from frost
 - Used at temperatures from 10°C-30°C
 - After use, work tools should be cleaned with water
 - Store the product in dry places and away from contact with the sun and heat sources
-

APPLICATION DETAILS:

New surface:

Apply a coat of graffiti primer and after about 12 hours it is done with graffiti

Plaster if necessary:

The walls is cleaned with water and then apply a coat of graffiti primer to the entire surface. After at least 12 hours, it is done with graffiti.

CHARACTERISTICS:

Bonding:	With Water-based resins
Visual aspect:	red thixotropic paste
Drying (at temp. 20°):	superficial 40 minutes
Full:	2 hours
Dilution:	With water up to 10-30%
Application:	Penello, roll,
Consumption:	7-9 m ² / first coat
Packaging:	5kg,20kg

All the above technical data are the fruit of our experience, they have a guiding character for the final result. The data in the technical tab can be changed based on possible changes in raw materials and production technology. Before using the product, we always advise that a preliminary test is done with the product*
