

Art.4000 ATAVIL D3

Wood glue for exterior and interior D3

GENERAL SPECIFICATIONS:

Water-based wood adhesive with excellent adhesion and resistant to water when dry in accordance with the standard EN 204 classified D3. Used for parquet, doors, windows, wooden furniture, suitable for gluing wood to wood where water resistance is required.

ADVICE:

- Protect the product from frost
 - It is used at temperatures above 10°C
 - Respect the drying time
 - Water resistance to be tested after 7 days
 - Applying a thin layer can lead to sticking of the adhesive
 - After use, work tools should be cleaned with water
 - Store the product in dry places and away from contact with the sun and heat sources
-

APPLICATION DETAILS:

Using the right materials, Atavil D3 is spread uniformly over the surface to be glued. The surfaces to be glued must be clean of dust and dirt. For exotic wood, it is recommended to paint with ATAVIL D3 on both surfaces to be glued.

Amount of glue it depends on the type of surface and material. After gluing, a pressure of 3-5 kg/cm² should be applied until the material dries.

CHARACTERISTICS:

Bonding:	With water-based resins
Visual aspect:	thick white liquid
Drying (at temp. 20°):	15-30 minutes
Use:	Brush, roller,
Consumption:	140-180gr/m ²
Confection:	4kg/20kg/130kg/1000kg

All the above technical data are the fruit of our experience, they have a guiding character for the final result. The data in the technical tab can be changed based on possible changes in raw materials and production technology. Before using the product, we always advise that a preliminary test is done with the product*
