

## Art.6020 **BETONKONTAKT**

Water-based primer for interior and exterior walls

---

### **GENERAL SPECIFICATIONS:**

Betonkontakt is a mixture of water-based synthetic materials with a high alkaline resistance, quartz sand and selected fillers. After application, the product increases the possibility of bonding of the mortar with the concrete and is diluted with water.

---

### **ADVICE:**

- Protect the product from frost
  - Used at temperatures from 10°C-30°C
  - After use, work tools should be cleaned with water
  - Store the product in dry places and away from contact with the sun and heat sources
- 

### **APPLICATION DETAILS:**

It is a product that is given with a roller before making the mortar on the concrete. The amount of water needed to help the good alignment is added to the bucket and the application is made. It must be dried and then the plaster directly.

---

### **CHARACTERISTICS:**

<b>Bonding:</b>	With water-based resins
<b>Visual aspect:</b>	Red thixotropic paste

---

<b>Drying (at temp. 20°):</b>	superficial 40 minutes
<b>Full:</b>	2 hours
<b>Dilution:</b>	With water up to 30%
<b>Application:</b>	Brush, roller
<b>Consumption:</b>	350gr/ m <sup>2</sup> with one hand
<b>Packaging:</b>	5kg, 20kg

---

All the above technical data are the fruit of our experience, they have a guiding character for the final result. The data in the technical tab can be changed based on possible changes in raw materials and production technology. Before using the product, we always advise that a preliminary test is done with the product\*

---