

Art 6002 **CASABIANCA**

Plastic paint for interior walls

GENERAL SPECIFICATIONS:

Paint based on aqueous resins, covering pigments, filler which allows the walls to breathe. It is used for painting various wall surfaces such as gypsum plaster, etc. It has a fairly good coverage and extension, it is used in white and light colors.

ADVICE:

- Protect the product from frost
 - Used at temperatures from 10°C-30°C
 - After use, work tools should be cleaned with water
 - Store the product in dry places and away from contact with the sun and heat sources
-

APPLICATION DETAILS:

New surface:

It is painted with one coat of fixocryl or murofix primer (water-based) and after at least 4 hours, it is painted with two coats of CASABIANCA paint diluted 15%-25% with water

Previously painted surface:

Painted with plastic paint: plastered and sanded with paper if it is necessary: clean the wall with a wet sponge and apply one coat of fixoril or murofix primer to the entire surface. After at least 4 hours, paint with two coats of paint CASABIANCA
Painted with hydromat or lime that can be removed: plastered and sanded with paper if necessary: clean the wall with a wet sponge and apply one coat of fixoril or murofix primer to the entire surface. After at least 4 hours, paint with two coats of CASABIANCA paint

CHARACTERISTICS:

Bonding:	With acrylic styrene resins
Visual aspect:	Thixotropic paste
Drying (at temp. 20°):	superficial 40 minutes
Full:	2 hours Second hand after 4 hours
Dilution:	With water up to 15-25%
Application:	Brush, roller, spray
Consumption:	7-8 m ² /lt with one hand
Packaging:	3lt,9lt,14lt

All the above technical data are the fruit of our experience, they have a guiding character for the final result. The data in the technical tab can be changed based on possible changes in raw materials and production technology. Before using the product, we always advise that a preliminary test is done with the product*
