

## Art 7005 **DOALSPACANTE**

Decorative paint for walls

---

### **GENERAL SPECIFICATIONS:**

DOALSPACANTE is a mixture of water-based polymers ideal for creating high-quality finishes with decorative effects (of aged, cracked paint)

---

### **ADVICE:**

- Protect the product from frost
  - Use at temperatures from 5°C-30 °C
  - After use, the work tools should be cleaned with water
  - Store the product in dry places and away from contact with the sun and heat sources
- 

### **APPLICATION DETAILS:**

The product can be applied on all types of surfaces, it is enough to treat them with the necessary products. Surface it must be linen, clean and oil-free. For a quality finish, the surface must be plastered.

Use an acrylic paint as background, which color is chosen opposite to the color of the finish. After complete drying, painting is done with a roller (like the one used for enamel, so with short hair).

DOALSPACANTE, diluted with water no more than 10%. It is important that this is given in a uniform way. It is left to dry for at least 12 hours and then painted with acrylic paint for finishing. During drying, cracks with dimensions of different according to the way the paint is applied and the type of tools used (roller or brush). The finish made with a brush. The finish made with a roller.

---



The finish is done with a brush



The finish is made with a roller

The regularity of the cracks depends on the uniformity of DOALSPACANTE.

The size of the cracks depends on the thickness of the finish. The bigger the thickness, the more visible the cracks.

---

## CHARACTERISTICS:

<b>Connection:</b>	With acrylic styrene resins
<b>Visual aspect:</b>	Thixotropic paste
<b>Drying (at temp. 20°):</b>	superficial 40 minutes
<b>Complete:</b>	4 hours
<b>Thinning:</b>	With water up to 10%
<b>Use:</b>	Brush, roller, spray
<b>Consumption:</b>	7-9 m <sup>2</sup> /lt
<b>Confection:</b>	0.75lt/2.5lt

---

All the above technical data are the fruit of our experience, they have a guiding character for the final result. The data in the technical tab can be changed based on possible changes in raw materials and production technology. Before using the product, we always advise that a preliminary test is done with the product\*

---