

## **Art.509 FINISH**

### Glossy wood paint

---

#### **GENERAL SPECIFICATIONS:**

Oil-based paint for painting iron wood as a final coat with a gloss resistant to atmospheric agents, water-resistant and good surface protector.

---

#### **ADVICE:**

- It is used in ventilated rooms
  - Do not use on hot surfaces or in direct sunlight
  - After use, work tools should be cleaned with oil
  - Store the product in dry places and away from contact with the sun and heat sources
  - Do not throw waste in open areas
- 

#### **APPLICATION DETAILS:**

The new surface The surface is cleaned and painted with one or two anti-moth coats, 24 hours apart from each other. After another 24 hours, the treated surface is painted with Art 509 as a final coat. The new surface The surface is cleaned from the debris and parts of the paint that have stuck. The surface is slightly abraded with a fine abrasive paper. It is cleaned with a wet cloth. After the entire surface has dried, then painting with Art 509 is done.

---

## CHARACTERISTICS:

<b>Binder:</b>	With oily resins
<b>Visual aspect:</b>	fluid thickens the lining
<b>Drying (at temp. 20°):</b>	surface 2 hours
<b>Complete:</b>	24-36 hours Second coat after 24 hours
<b>Thinning:</b>	With oil max 10%
<b>Use:</b>	Brush, roller, spray
<b>Consumption:</b>	14-16 m <sup>2</sup> /lt with one hand
<b>Packaging:</b>	0.75lt, 2.5lt

---

All the above technical data are the fruit of our experience, they have a guiding character for the final result. The data in the technical tab can be changed based on possible changes in raw materials and production technology. Before using the product, we always advise that a preliminary test is done with the product\*

---