

## Art 8000 **FIXOCRIL**

Water-based primer for interior walls

---

### **GENERAL SPECIFICATIONS:**

Transparent hardening primer for external surfaces used before painting. It unifies the absorbency of the surface and improves the connection of the wall surface with the paint and thinned with oil.

---

### **ADVICE:**

- Protect the product from frost
  - Used at temperatures from 10°C-30°C
  - After use, work tools should be cleaned with water
  - Store the product in dry places and away from contact with the sun and heat sources
- 

### **APPLICATION DETAILS:**

#### **New surface:**

A coat of fixocryl primer is applied and after about 4 hours, the painting should be done with the paint chosen for painting

#### **Previously painted surface:**

It is plastered and sanded with paper if necessary: the wall is cleaned with a wet sponge and is applied a coat of fixoril primer to the entire surface. After at least 4 hours, the wall is painted with the paint chosen for painting

---

## CHARACTERISTICS:

<b>Bonding:</b>	With water-based resins
<b>Visual aspect:</b>	Thixotropic paste
<b>Drying (at temp. 20°):</b>	superficial 40 minutes
<b>Full:</b>	2 hours Second hand after 4 hours
<b>Dilution:</b>	With water up to 50%-200%
<b>Application:</b>	Brush, roller, spray
<b>Consumption:</b>	8-10 m <sup>2</sup> /lt with one hand
<b>Packaging : 3</b>	3lt, 9lt, 14, lt

---

All the above technical data are the fruit of our experience, they have a guiding character for the final result. The data in the technical tab can be changed based on possible changes in raw materials and production technology. Before using the product, we always advise that a preliminary test is done with the product\*

---