

Art 7000 **FONDODEKOR**

Primer for decorative work

GENERAL SPECIFICATIONS:

Paint based on titanium dioxide synthetic resins and special fillers, for painting various wall surfaces before painting with decorative paints

ADVICE:

- Protect the product from frost
 - Used at temperatures from 10°C-30°C
 - After use, work tools should be cleaned with water
 - Store the product in dry places and away from contact with the sun and heat sources
-

APPLICATION DETAILS:

New surface:

It is painted with one coat of water-based primer and after at least 4 hours, it is painted with one coat of FONDART paint diluted 10%-20% with water. After at least 12 hours, should be made the application with the selected decorative paint

Previously painted surface:

Painted with plastic paint: plastered and sanded with paper if it is necessary: clean the wall with a wet sponge and apply one coat of primer to the entire surface. After at least 4 hours, paint with one coat of FONDART paint. After at least 12 hours, apply the chosen decorative paint

Painted with hydromat or lime that can be removed:

plastered and sanded with paper if necessary: clean the wall with a wet sponge and apply a coat of fixoril or murofix primer to the entire surface. After at least 4 hours, paint with a coat of FONDART paint. After at least 12 hours, apply the chosen decorative paint

CHARACTERISTICS:

Bonding:	With styrene acrylic resin
Visual aspect:	thixotropic paste
Drying (at temp. 20°):	superficial 40 minutes
Full:	4 hours
Dilution:	With water up to 10-20%
Application:	Penello, roll, and spray
Consumption:	7-9 m ² /lt
Packaging:	3lt,9lt

All the above technical data are the fruit of our experience, they have a guiding character for the final result. The data in the technical tab can be changed based on possible changes in raw materials and production technology. Before using the product, we always advise that a preliminary test is done with the product*
