

Art 6006 MASTER

Washable paint for inside and outside

GENERAL SPECIFICATIONS:

Water-based paint with synthetic binder with very high whiteness and coverage, easy to use. Resistant to washing and atmospheric agents. Used on all types of surfaces previously treated with primer. relevant. It is used with all types of colors.

ADVICE:

- Protect the product from frost
 - Use at temperatures from 10°C-30°C
 - After use, clean the work tools with water
 - Store the product in dry places and away from contact with the sun and heat sources
-

APPLICATION DETAILS:

New surface:

Painted with one coat of water-based primer and after at least 4 hours, painted with two coats of MASTER paint diluted with 20%-30% water

Previously painted surface:

Painted with plastic paint:

putty and sand with paper if necessary: clean the wall with a wet sponge and apply one coat of fixoril or murofix primer to the entire surface. After at least 4 hours, paint with two coats of MASTER paint

Painted with hydromat or lime that can be wiped away:

puttyed and sanded with paper if necessary: clean the wall with a wet sponge and apply one coat of fixoril or murofix primer to the entire surface. After at least 4 hours, paint with two coats of MASTER paint

CHARACTERISTICS:

Bonding:	With acrylic styrene resins
Visual aspect:	Thixotropic paste
Drying (at temp. 20°):	superficial 40 minutes
Complete:	2 hours Second coat after 4 hours
Thinning:	With water up to 20-30%
Use:	Brush, roller, spray
Consumption:	12-14 m ² /lt with one hand
Confection:	3lt,9lt,14lt

All the above technical data are the fruit of our experience, they have a guiding character for the final result. The data in the technical tab can be changed based on possible changes in raw materials and production technology. Before using the product, we always advise that a preliminary test is done with the product*
