

Art 510 METALOX

Decorative paint for painting iron

GENERAL SPECIFICATIONS:

Oil-based resin-based paint with anti-UV additive and special fillers for painting iron with antique effect.

ADVICE:

- It is used in ventilated environments
 - Do not use on hot surfaces or on surfaces exposed to direct sunlight
 - after use, work tools should be cleaned with neft cleaner
 - Store the product in dry places and away from contact with the sun and heat sources
 - Do not throw waste in open areas
-

APPLICATION DETAILS:

The new surface

The surface is cleaned of rust with a wire brush or paper and then with a cloth moistened with oil, it is passed over the entire surface to remove dust. After the surface is dry, it is passed with a brush with Art 522 and at least after 12 hours, comes the second coat. After another 12-24 hours, apply Metalox with two hands, leaving one coat to dry from the other

Painted surfaces

The surface is cleaned of debris and parts of the paint that have stuck and then with a cloth wet with oil it is passed over the entire surface to remove the dust, after the surface is dry it is passed with a brush one coat with Art 522 and at least after 12 hours apply with the second coat. After another 12-24 hours, paint with two coats of Metalox, leaving one coat to dry from the other

CHARACTERISTICS:

Binder:	With oily resins
Visual aspect:	gray, red, white, black liquid
Drying (at temp. 20°):	superficial 2 hours
Complete:	24-36 hours, Second hand after 24 hours
Dilution:	Ready to use
Use:	Brush, roller, spray
Consumption:	7-10 m ² /lt with one hand
Packaging:	1 kg, 5 kg

All the above technical data are the fruit of our experience, they have a guiding character for the final result. The data in the technical tab can be changed based on possible changes in raw materials and production technology. Before using the product, we always advise that a preliminary test is done with the product*
