

Art 6006 MONOMANO

Washable paint for indoor and outdoor use

GENERAL SPECIFICATIONS:

Synthetic binder-based water-based paint with very high whiteness and coverage, easy to use resistant to washing and atmospheric agents. It is used on all types of surfaces previously treated with the corresponding primer. Suitable for indoor and outdoor surfaces.

ADVICE:

- Protect the product from frost
- Used at temperatures from 10°C-30°C
- After use, work tools should be cleaned with water
- Store the product in dry places and away from contact with the sun and heat sources

APLICATION DETAILS:

The new surface

It is painted with one coat of water-based primer and after at least 4 hours, it is painted with two coats of MONOMANO diluted 20-30% with water.

Previously painted surface: it is plastered and sanded with paper if necessary: the wall is cleaned with a wet sponge and a coat of fixoril or murofix primer is applied to the entire surface. After at least 4 hours, it is painted with two coats of MONOMANO paint Painted with hydromat or lime that can be wiped away: puttyed and sanded with paper if necessary: clean the wall with a wet sponge and apply one coat of fixoril or murofix primer to the entire surface. After at least 4 hours, paint with two coats of MONOMANO paint

Adress: Zona industriale, 3001, Elbasan

Tel: +355 58 32 6066/1, E-mail: doalpaint@doalpaint.com web: www.doalpaint.com



CHARACTERISTICS:

Bonding: With acrylic styrene resins

Visual aspect: Thixotropic paste

Drying (at temp. 20°): superficial 40 minutes

Full: 2 hours Second coat after 4 hours

Dilution: With water up to 20-30%

Application: Brush, roller, spray

Consumption: 12-14 m²/lt with one coat

Packaging: 3lt,9lt,14lt

All the above technical data are the fruit of our experience, they have a guiding character for the final result. The data in the technical tab can be changed based on possible changes in raw materials and production technology. Before using the product, we always advise that a preliminary test is done with the product*

Adress: Zona industriale, 3001, Elbasan

Tel: +355 58 32 6066/1, E-mail: doalpaint@doalpaint.com web: www.doalpaint.com