

Art.6011 MUROFIX

Water-based primer for interior and exterior walls

GENERAL SPECIFICATIONS:

Hardening primer for interior and exterior surfaces to be used prior to painting. It unifies the absorbency of the surface and improves the adhesion of the wall surface to the paint. It is diluted with water

ADVICE:

- Protect the product from frost
 - Used at temperatures from 10°C-30°C
 - After use, work tools should be cleaned with water
 - Store the product in dry places and away from contact with the sun and heat sources
-

APPLICATION DETAILS:

New surface:

Apply s coat of Murofix primer and after about 4 hours, should be done the painting with the paint chosen for painting

Previously painted surface:

Plaster and sanded with paper if necessary: The walls is cleaned with water and then apply a coat of Murofix primer to the entire surface. After at least 4 hours, should be done with the paint chosen for painting

CHARACTERISTICS:

Bonding:	With Water-based resins
Visual aspect:	white liquid
Drying (at temp. 20°):	superficial 40 minutes
Full:	2 hours. Second coat after 4 hours
Dilution:	With water up to 50%-400%%
Application:	Penello, roll, sphy
Consumption:	18-25 m ² /lt first coat
Packaging:	3lt, 9lt, 14lt

All the above technical data are the fruit of our experience, they have a guiding character for the final result. The data in the technical tab can be changed based on possible changes in raw materials and production technology. Before using the product, we always advise that a preliminary test is done with the product*
