

Art993 PROTECT

Antimol for painting wood

GENERAL SPECIFICATIONS:

Oil-based anti-molding protection for wood for interior or exterior painting with color or transparent

ADVICE:

- It is used in ventilated rooms
 - Do not use on hot surfaces or in direct sunlight
 - After use, work tools should be cleaned with oil
 - Store the product in dry places and away from contact with the sun and heat sources
 - Do not throw waste in open areas
-

APPLICATION DETAILS:

The new surface The surface is cleaned and painted with one or two anti-moth coats, 24 hours apart. Painted surfaces The surface is cleaned from the bemurins and the parts of the paint that have stuck. The surface is lightly abraded with a fine abrasive paper. It is cleaned with a cloth moistened with oil. After the entire surface is dry, then the painting is done with one or two hands,

CHARACTERISTICS:

Connection:	With oily resins
Visual aspect:	liquid
Drying (at temp. 20°):	superficial 2 hours
Full:	24-36 hours Second coat after 24 hours
Dilution:	Ready to use
Use:	Brush, roller, spray
Consumption:	14-16 m ² /lt with one hand
Packaging:	0.75lt, 2.5lt

All the above technical data are the fruit of our experience, they have a guiding character for the final result. The data in the technical tab can be changed based on possible changes in raw materials and production technology. Before using the product, we always advise that a preliminary test is done with the product*
