

## **SILODECOR**

Outdoor acrylic paint

---

### **GENERAL SPECIFICATIONS:**

It is a water-repellent paint based on water-based resins and selected ingredients, for painting all types of surfaces: plaster, plaster, wood, iron, previously treated with the relevant primers, which give this paint characteristics such as: A point of very high whiteness. Pretty good coverage. A fairly good pretending and water repellency.

---

### **ADVICE:**

- Protect the product from frost
  - Used at temperatures from 10°C-30°C
  - Do not use on hot surfaces or in direct sunlight
  - It is preferable that the painted surface be protected from rain in the first 48 hours after painting
  - After use, work tools should be cleaned with water
  - Store the product in dry places and away from contact with the sun and heat sources
- 

### **USAGE:**

New surface:

Surfaces with new plaster must be painted 30/40 days after plastering. It is painted with one coat of water or oil-based primer and after at least 12 hours, it is painted with two coats of paint diluted with 20%-30% water.

---

### Old surface

Painted or not previously painted: sand with a metal brush and remove all stuck surfaces, wash the wall surface with low pressure water and let it dry. Correct the damaged parts of the wall with putty or grout and let it dry. it dries well. One coat of murofix primer is applied to the entire surface. After at least 12 hours, it is painted with two coats of paint

---

### **CHARACTERISTICS:**

Bonding: With acrylic styrene resins

Visual aspect: Thixotropic paste

Drying (at temp. 20°): superficial 40 minutes

Full: 2 hours

Second coat after 4 hours

Dilution: With water up to 20-30%

Application: Brush, roller, spray

Consumption: 10-12 m<sup>2</sup>/lt with one coat

Packaging: 3lt,10lt,14,lt