

Art 534 STONFINISH

Transparent paint for stone, concrete with fast drying

GENERAL SPECIFICATIONS:

Transparent paint based on quick-drying acrylic binder for painting surfaces of concrete, stone, brick, etc. To protect against atmospheric agents.

ADVICE:

- Beware of the gases created
 - After use, work tools should be cleaned with nitro cleaner
 - Store the product in dry places and away from contact with the sun and heat sources
 - Do not throw waste in open areas
-

APPLICATION DETAILS:

The surface which will be treated with paint must be clean of dust, oils and dry from water. The ambient temperature must be between 10°C-35°C. The relative humidity of the air 75%. The product is given with a brush, roller or pistol

CHARACTERISTICS:

Binder:	Water-repellent acrylic resin
Visual aspect:	thin transparent liquid
Drying (at temp. 20°):	superficial 1 hour
Complete:	4-5 hours
Dilution:	max 10%
Use:	Brush, roller, spray
Consumption:	7-10 m ² /lt with one hand
Packaging:	0.75lt, 5lt, 20lt
Pom diameter:	0.41-0.58 mm.
Thinner:	0-5% Epoxy thinner

All the above technical data are the fruit of our experience, they have a guiding character for the final result. The data in the technical tab can be changed based on possible changes in raw materials and production technology. Before using the product, we always advise that a preliminary test is done with the product*
