

Art 7002 VELATURA

Decorative paint for walls

GENERAL SPECIFICATIONS:

Paint with a special binder and filler for use as a decorative finish on walls. In addition to the protection it gives to the wall, it also decorates it, giving it an antique aesthetic effect. It is used in a variety of colors based on the catalog. The natural mineral that creates the antique effect has a changing aspect, so the works always remain unique and unrepeatable.

ADVICE:

- Protect the product from frost
- Used at temperatures from 5°C-30°C
- After use, work tools should be cleaned with water
- Store the product in dry places and away from contact with the sun and heat sources

APLICATION DETAILS:

The product can be applied on all types of surfaces, it is enough to treat them with the necessary products. The surface must be smooth, clean and oil-free. For a quality finish, the surface must be plastered.

New surface:

It is painted with one hand of water-based primer and after at least 4 hours, it is painted with two hands of paint with the color we have chosen. After at least 12 hours, the application is made with VELATURA decorative paint, which is mixed with pigment to achieve the color of requested. and it is applied with a glove or a brush, rotating the hand in a circular way and thus leaving the light and shadows on the walls.

Adress: Zona industriale, 3001, Elbasan

Tel: +355 58 32 6066/1, E-mail: doalpaint@doalpaint.com web: www.doalpaint.com



Previously painted surface:

Painted: plastered and sanded with paper if necessary: clean the wall with a wet sponge and apply one coat of primer to the entire surface. After at least 4 hours, paint with one coat of FONDART paint. It is painted with one hand of water-based primer and after at least 4 hours, it is painted with two hands of paint with the color we have chosen. After at least 12 hours, the application is made with VELATURA decorative paint, which is mixed with pigment to achieve the desired color. and it is applied with gloves or a brush by rotating the hand in a circular manner and thus leaving light shadows on the walls

CHARACTERISTICS:

Connection:	With styrene acrylic resins
Visual aspect:	Transparent paste
Drying (at a temperature of 20°):	12-24 hours
Thinning:	according to desire
Use :	Penello
Consumption:	0.100-0.300gr/m ²
Confection :	0.75lt/2.5lt

All the above technical data are the fruit of our experience, they have a guiding character for the final result. The data in the technical tab can be changed based on possible changes in raw materials and production technology. Before using the product, we always advise that a preliminary test is done with the product*