

Art 8009 DOALTEK

Paint for painting tiles

GENERAL SPECIFICATIONS:

Water-based paint based on special acrylic binder with very high coverage, satin appearance, easy to use. Resistant to washing and atmospheric agents. It is used in the industry of concrete tile production.

ADVICE:

- Protect the product from frost
 - Used at temperatures from 5°C-30°C
 - Do not use on surfaces that are hot or in direct sunlight
 - After use, work tools should be cleaned with water
 - Store the product in dry places and away from contact with the sun and heat sources
-

APPLICATION DETAILS:

New tile:

It is painted without primer directly after production, diluted with a maximum of 5% water

Old tile:

they are scraped with a metal brush and all the stuck surfaces are removed, and the mold is washed away surface with high-pressure water and allow to dry.

Apply murofix primer all over the surface.

After at least 12 hours with paint

CHARACTERISTICS:

Bonding:	With acrylic resins
Visual aspect:	Thixotropic paste
Drying (at temp. 20°):	superficial 40 minutes
Full:	2 hours
Dilution:	With water up to 5%
Application:	Brush, roller, spray
Consumption:	350gr/lt

All the above technical data are the fruit of our experience, they have a guiding character for the final result. The data in the technical tab can be changed based on possible changes in raw materials and production technology. Before using the product, we always advise that a preliminary test is done with the product*
