

Art.6010 **MURODUR**

Oil-based primer for exterior walls

GENERAL SPECIFICATIONS:

Transparent hardening primer for exterior surfaces to be used before painting. It unifies the absorbency of the surface and improves the adhesion of the wall surface to the paint and thinned with oil.

ADVICE:

- Used at temperatures from 10°C-30°C
 - It is very important to adjust the dilution ratio so that the surface painted with the primer does not come out shiny as it reduces the binding ability of the paint to the wall, it must always be a matte surface.
 - After use, work tools should be cleaned with oil
 - Store the product in dry places and away from contact with the sun and heat sources
-

APPLICATION DETAILS:

New surface:

Apply s coat of Murodur primer and after about 4 hours, should be done the painting with the paint chosen for painting

Previously painted surface:

Plaster and sanded with paper if necessary: The walls is cleaned with water and then apply a coat of Murodur primer to the entire surface. After at least 4 hours, should be done with the paint chosen for painting

CHARACTERISTICS:

Bonding:	oils resins
Visual aspect:	thixotropic paste
Drying (at temp. 20°):	superficial 40 minutes
Full:	2 hours
Dilution:	100:100 with white spirit
Application:	Penello, roll, spry
Consumption:	8-10 m ² /lt first coat
Packaging:	4lt + 4lt

All the above technical data are the fruit of our experience, they have a guiding character for the final result. The data in the technical tab can be changed based on possible changes in raw materials and production technology. Before using the product, we always advise that a preliminary test is done with the product*
