

# Art 901/902 PRIMER EPOX

## Transparent concrete primer

#### **GENERAL SPECIFICATIONS:**

Art 901/902 PRIMER EPOX is a two-component epoxy-based paint with a polyamide dryer for concrete floors that will be treated with epoxy resin coating.

#### ADVICE:

- Beware of the gases created
- After use, work tools should be cleaned with polyurethane cleaner or alcohol
- Store the product in dry places and away from direct sunlight heat sources
- Do not dispose of waste in open areas

### **USAGE:**

#### Surface preparation:

Clean the surface with a wire brush or sandpaper, in order to remove dirt and stackable parts. The product is catalyzed 1:1.

It can be applied: with a brush, roller, spray

The mixture is done slowly and uniformly in order to have uniform characteristics for the entire surface Theoretical Consumption 8-10 m²/liter

Adress: Zona industriale, 3001, Elbasan

Tel: +355 58 32 6066/1, E-mail: doalpaint@doalpaint.com web: www.doalpaint.com



### **CHARACTERISTICS:**

**Bonding:** With epoxy resins

Visual aspect: gray liquid

**Drying (at temp. 20°):** superficial 20 minutes

**Dilution A: Dilution B** Dilution B 100:100

**Application:** Penello, roll, spry

Packaging: 5kg,20kg

Adress: Zona industriale, 3001, Elbasan

Tel: +355 58 32 6066/1, E-mail: doalpaint@doalpaint.com web: www.doalpaint.com